

FS Section	Content field	Explanation of content	CSR	eSDS
1. Title	1.1 Title of SPERC	Use as a fuel (professional): solvent-borne	Y	Y
	1.2 SPERC code	ESVOC SPERC 9.12b.v3	Y	Y
2. Scope	<b>2.1 Substance/Product Domain</b>			
	Substance types / functions / properties included or excluded	Applicable to petroleum substances and petrochemicals.	Y	N
	Additional specification of product types covered:	Includes a variety of aliphatic and aromatic hydrocarbons, ketones, alcohols, acetates, glycols, glycol ethers, and glycol ether acetates.	Y	N
	Inclusion of sub-SPERCs	No	N	N
	<b>2.2 Process domain</b>			
	Description of activities/processes:	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste and consumer uses in liquid fuels.	Y	Y
	<b>2.3 List of applicable Use Descriptors</b>			
	LCS	PW – Widespread use by professional workers	Y	Y
	SU	SU8 – Manufacture of bulk large-scale chemicals (including petroleum products)	Y	Y
PC	PC13 – Fuels	Y	Y	
3. Operational conditions	<b>3.1 Conditions of use</b>			
	Location of use	Indoor/Outdoor	Y	Y
	Water contact during use	Yes	Y	Y
	Connected to a standard municipal biological STP	Yes	Y	Y
	Rigorously contained system with minimisation of release to the environment	No	Y	N
	Further operational conditions impacting on releases to the environment	Volatile compounds prone to atmospheric release. Wastewater emissions generated from equipment cleaning with water.	Y	Y
	<b>3.2 Waste Handling and Disposal</b>			
Waste Handling and Disposal:	Unused and spent products and solutions should be appropriately labelled and stored for eventual recovery or disposal as hazardous waste. A suitable unbreakable and closable container should be used when storing and shipping hazardous materials. The containers must be solvent compatible, leakproof, and free of any defects. Contaminated debris such as disposable paper towels, brushes, rollers, masks, transfer vessels, and wipes that may contain small amounts of solvent residue need to be handled as hazardous waste and properly disposed of in a manner that is consistent with local, regional, and national regulations. Direct disposal of waste into a municipal sewer system needs to conform with all applicable laws and regulations. A spill plan needs to be available that outlines the steps to be taken to minimize any potential health and environmental threats. EPA (2001). Managing Your Hazardous Waste: A Guide for Small Businesses. U.S. Environmental Protection Agency, Office of Solid Waste	Y	N	

FS Section	Content field	Explanation of content	CSR	eSDS
		and Emergency Response. Washington, DC. <a href="https://www.epa.gov/sites/production/files/2014-12/documents/k01005.pdf">https://www.epa.gov/sites/production/files/2014-12/documents/k01005.pdf</a> .		
4. Obligatory RMMs onsite	RMM limiting release to air:	No obligatory RMMs.	Y	Y
	RMM Efficiency (air):	Emissions to air are minimized when the product is used in accordance with the manufacturers' instructions and specifications.	Y	Y
	Reference for RMM Efficiency (air):	TSSA (2018). Procedure for the Handling of Fuel at Construction Sites. Technical Standards and Safety Authority, Civil Engineering Sector Labour-Management Health and Safety Committee. Toronto, Canada.	Y	N
	RMM limiting release to water:	By default, the release to water is modified after biological treatment at a standard municipal sewage treatment plant (STP) with an effluent flow rate of 2,000 m <sup>3</sup> /day. The effluent discharge rate is applicable to a group of 10,000 inhabitants who generate 200 L of wastewater per person.	Y	Y
	RMM Efficiency (water):	The removal efficiency is provided by the SimpleTreat model, which takes into consideration the biodegradability, partitioning behaviour, and volatility of an organic substance. Degradation assumes the operation of an aerobic activated-sludge reactor under steady-state conditions.	Y	Y
	Reference for RMM Efficiency (water):	ECHA (2016). <a href="https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf">Guidance on Information Requirements and Chemical Safety Assessment. Chapter R.16: Environmental Exposure Assessment</a> Version 3.0. European Chemicals Agency. Helsinki, Finland. <a href="https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf">https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf</a>	Y	N
	RMM limiting release to soil:	No obligatory RMMs.	Y	Y
	RMM Efficiency (soil):	Emissions to soil are minimized when the product is used in accordance with the manufacturers' instructions and specifications.	Y	Y
	Reference for RMM Efficiency (soil):	TSSA (2018). Procedure for the Handling of Fuel at Construction Sites. Technical Standards and Safety Authority, Civil Engineering Sector Labour-Management Health and Safety Committee. Toronto, Canada.	Y	N
5. Exposure Assessment Input	<b>5.1 Substance use rate</b>			
	Amount of substance use per day:	Supplied by registrant	Y	Y
	Fraction of EU tonnage used in region:	10% (default value)	Y	N
	Fraction of Regional tonnage used locally:	0.05% (default value)	Y	N
	Justification / information source:	ECHA (2016). <a href="https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf">Guidance on Information Requirements and Chemical Safety Assessment. Chapter R.16: Environmental Exposure Assessment</a> Version 3.0. European Chemicals Agency. Helsinki, Finland. <a href="https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf">https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf</a>	Y	N
	<b>5.2 Days emitting</b>			
	Number of emission days per year:	365 (default value)	Y	Y
	Justification / information source:	ECHA, 2016. <a href="https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf">Guidance on Information Requirements and Chemical Safety Assessment. Chapter R.16: Environmental Exposure Assessment</a> Version 3.0. European Chemicals Agency. Helsinki, Finland. <a href="https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf">https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf</a>	Y	N
	<b>5.3 Release factors</b>			
	sub-SPERC identifier:	ESVOC 9.12b.v3	Y	N
ERC	ERC 9a ERC 9b			
sub-SPERC applicability:	None	Y	N	

FS Section	Content field	Explanation of content	CSR	eSDS
<b>5.3.1 Release Factor – air</b>				
	<b>Numeric value / percent of input amount (Air)</b>	0.5%	Y	Y
	<b>Justification of RFs (Air):</b>	<p>The value has been derived from published emission factors for the combustion of different fuel types; including gasoline, diesel, and kerosene. Those exhaust and/or evaporative emissions reported in grams per mile were converted to grams per gram of fuel combusted by adjusting for the average fuel efficiency in the applicable vehicle fleet. ANL (2015). The GREET Model Expansion for Wheels-to Wheels Analysis of Heavy-Duty Vehicles. Argonne National Laboratory. Argonne, IL. <a href="https://greet.es.anl.gov/publication-heavy-duty">https://greet.es.anl.gov/publication-heavy-duty</a></p> <p>EASA (2019). ICAO Aircraft Engine Emissions Databank. European Union Aviation Safety Agency. Cologne, Germany. July 30, 2019. <a href="https://www.easa.europa.eu/easa-and-you/environment/icao-aircraft-engine-emissions-databank">https://www.easa.europa.eu/easa-and-you/environment/icao-aircraft-engine-emissions-databank</a></p>	Y	N
<b>5.3.2 Release Factor – water</b>				
	<b>Numeric value / percent of input amount (Water):</b>	0.0001%	Y	Y
	<b>Justification of RFs (Water):</b>	<p>The water and soil release factors examined the fuel spillages at service stations using conventional dispensing equipment with no vapor recovery capabilities. The lost fuel was distributed to water and soil after adjusting for the amount available for evaporation. Partitioning to the remaining environmental compartments was estimated using a multimedia fugacity model.</p> <p>Morgester, J.J., et al. (1992). Comparison of spill frequencies and amounts at vapor recovery and conventional service stations in California. <i>Journal of the Air &amp; Waste Management Association</i> 42, 284-289.</p> <p>Hilpert, M., and Breyse, P.N. (2014). Infiltration and evaporation of small hydrocarbon spills at gas stations. <i>Journal of Contaminant Hydrology</i> 170, 39-52.</p>	Y	N
<b>5.3.3 Release Factor – soil</b>				
	<b>Numeric value / percent of input amount (Soil):</b>	0.025%	Y	Y
	<b>Justification of RFs (Soil):</b>	<p>The water and soil release factors examined the fuel spillages at service stations using conventional dispensing equipment with no vapor recovery capabilities. The lost fuel was distributed to water and soil after adjusting for the amount available for evaporation. Partitioning to the remaining environmental compartments was estimated using a multimedia fugacity model.</p> <p>Morgester, J.J., et al. (1992). Comparison of spill frequencies and amounts at vapor recovery and conventional service stations in California. <i>Journal of the Air &amp; Waste Management Association</i> 42, 284-289.</p> <p>Hilpert, M., and Breyse, P.N. (2014). Infiltration and evaporation of small hydrocarbon spills at gas stations. <i>Journal of Contaminant Hydrology</i> 170, 39-52.</p>	Y	N
<b>5.3.4 Release Factor – waste</b>				
	<b>Percent of input amount disposed as waste:</b>	2%	Y	N
	<b>Justification of RFs:</b>	<p>The waste factor has been taken from a life cycle assessment of gasoline production and use in passenger cars (Morales, 2015). The evaluation revealed that 2.1 ml of hazardous waste was incinerated per km driven. The stated fuel mileage of 150 ml/km yields a waste release factor of 1.4%, which was rounded upward to 2%. An uncertainty factor has not been applied to this value since the waste associated with industrial fuel use is expected to be less than the value obtained for this comprehensive analysis.</p>	Y	N

FS Section	Content field	Explanation of content	CSR	eSDS
		Morales, M. et al. (2015). Life cycle assessment of gasoline production and use in Chile. <i>Science of the Total Environment</i> 505, 833-843		
<b>References to SPERC Background Document</b>				
	Reference to Background Document	ESIG/ESVOC (2019). SpERC Background Document. Specific Environmental Release Categories (SpERCs) for the professional use of solvents and solvent-borne substances in high release lubricants, metalworking fluids, fuels, and low release lubricants. European Solvents Industry Group. Brussels, Belgium.	Y	N