

FS Section	Content field	Explanation of content	CSR <sup>1</sup>	eSDS <sup>2</sup>
1. Title	1.1 Title of SPERC	Laboratory reagents (professional): solvent-borne	Y	Y
	1.2 SPERC code	ESVOC SPERC 8.17.v2	Y	Y
2. Scope	<b>2.1 Substance/Product Domain</b>			
	Substance types / functions / properties included or excluded	Applicable to petroleum substances and petrochemicals.	Y	N
	Additional specification of product types covered:	Includes a variety of aliphatic and aromatic hydrocarbons, ketones, alcohols, acetates, glycols, glycol ethers, and glycol ether acetates.	Y	N
	Inclusion of sub-SPERCs	No	N	N
	<b>2.2 Process domain</b>			
	Description of activities/processes:	Covers the use of small quantities within laboratory settings, including material transfers and equipment cleaning.	Y	Y
	<b>2.3 List of applicable Use Descriptors</b>			
	LCS	PW – Widespread use by professional workers	Y	Y
	SU	SU24 – Scientific research and development	Y	Y
	PC	PC21 – Laboratory chemicals	Y	Y
3. Operational conditions	<b>3.1 Conditions of use</b>			
	Location of use	Indoor	Y	Y
	Water contact during use	Yes	Y	Y
	Connected to a standard municipal biological STP	Yes	Y	Y
	Rigorously contained system with minimisation of release to the environment	No	Y	N
	Further operational conditions impacting on releases to the environment	Volatile compounds prone to atmospheric release. Wastewater emissions generated from equipment cleaning with water.	Y	Y
	<b>3.2 Waste Handling and Disposal</b>			
	Waste Handling and Disposal:	Unused and spent products and solutions should be appropriately labelled and stored for eventual recovery or disposal as hazardous waste. A suitable unbreakable and closable container should be used when storing and shipping hazardous materials. The containers must be solvent compatible, leakproof, and free of any defects. Contaminated debris such as disposable paper towels, brushes, rollers, masks, transfer vessels, and wipes that may contain small amounts of solvent residue need to be handled as hazardous waste and properly disposed of in a manner that is consistent with local, regional, and national regulations. Direct disposal of waste into a municipal sewer system needs to conform with all applicable laws and regulations. A spill plan needs to be available that outlines the	Y	N

<sup>1</sup> Explanations that are more detailed can be provided for the CSR..

<sup>2</sup> For the ES for communication a standard phrase may be selected from the ECom catalogue when available. When no phrase is available yet in the catalogue the proposed phrase can be reported here.

FS Section	Content field	Explanation of content	CSR <sup>1</sup>	eSDS <sup>2</sup>
		steps to be taken to minimize any potential health and environmental threats. EPA (2001). Managing Your Hazardous Waste: A Guide for Small Businesses. U.S. Environmental Protection Agency, Office of Solid Waste and Emergency Response. Washington, DC. <a href="https://www.epa.gov/sites/production/files/2014-12/documents/k01005.pdf">https://www.epa.gov/sites/production/files/2014-12/documents/k01005.pdf</a> .		
4. Obligatory RMMs onsite	RMM limiting release to air:	No obligatory RMMs.	Y	Y
	RMM Efficiency (air):	Emissions to air are minimized when the product is used in accordance with established practices.	Y	Y
	Reference for RMM Efficiency (air):	USEPA (2000). Environmental Management Guide for Small Laboratories. EPA 233-B-00-001, U.S. Environmental Protection Agency, Small Business Division. Washington, DC. <a href="https://nepis.epa.gov/Exe/ZyPDF.cgi/100049DH.PDF?Dockey=100049DH.PDF">https://nepis.epa.gov/Exe/ZyPDF.cgi/100049DH.PDF?Dockey=100049DH.PDF</a>	Y	N
	RMM limiting release to water:	By default, the release to water is modified after biological treatment at a standard municipal sewage treatment plant (STP) with an effluent flow rate of 2,000 m <sup>3</sup> /day. The effluent discharge rate is applicable to a group of 10,000 inhabitants who generate 200 L of wastewater per person.	Y	Y
	RMM Efficiency (water):	The removal efficiency is provided by the SimpleTreat model, which takes into consideration the biodegradability, partitioning behaviour, and volatility of an organic substance. Degradation assumes the operation of an aerobic activated-sludge reactor under steady-state conditions.	Y	Y
	Reference for RMM Efficiency (water):	ECHA (2016). <a href="https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf">Guidance on Information Requirements and Chemical Safety Assessment. Chapter R.16: Environmental Exposure Assessment</a> Version 3.0. European Chemicals Agency. Helsinki, Finland. <a href="https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf">https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf</a>	Y	N
	RMM limiting release to soil:	No obligatory RMMs.	Y	Y
	RMM Efficiency (soil):	Emissions to soil are minimized when the product is used in accordance with the manufacturers' instructions and/or the established practices.	Y	Y
	Reference for RMM Efficiency (soil):	USEPA (2000). Environmental Management Guide for Small Laboratories. EPA 233-B-00-001, U.S. Environmental Protection Agency, Small Business Division. Washington, DC. <a href="https://nepis.epa.gov/Exe/ZyPDF.cgi/100049DH.PDF?Dockey=100049DH.PDF">https://nepis.epa.gov/Exe/ZyPDF.cgi/100049DH.PDF?Dockey=100049DH.PDF</a>	Y	N
5. Exposure Assessment Input	5.1 Substance use rate			
	Amount of substance use per day:	Supplied by registrant	Y	Y
	Fraction of EU tonnage used in region:	10% (default value)	Y	N
	Fraction of Regional tonnage used locally:	0.05% (default value)	Y	N
	Justification / information source:	ECHA (2016). <a href="https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf">Guidance on Information Requirements and Chemical Safety Assessment. Chapter R.16: Environmental Exposure Assessment</a> Version 3.0. European Chemicals Agency. Helsinki, Finland. <a href="https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf">https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf</a>	Y	N
	5.2 Days emitting			
	Number of emission days per year:	365 (default value)	Y	Y
	Justification / information source:	ECHA, 2016. <a href="https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf">Guidance on Information Requirements and Chemical Safety Assessment. Chapter R.16: Environmental Exposure Assessment</a> Version 3.0. European Chemicals Agency. Helsinki, Finland. <a href="https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf">https://echa.europa.eu/documents/10162/13632/information_requirements_r16_en.pdf</a>	Y	N

FS Section	Content field	Explanation of content	CSR <sup>1</sup>	eSDS <sup>2</sup>
	<b>5.3 Release factors</b>			
	<b>sub-SPERC identifier:</b>	<b>ESVOC 8.17.v2</b>	Y	N
	ERC	ERC 8a		
	<b>sub-SPERC applicability:</b>	None	Y	N
	<b>5.3.1 Release Factor – air</b>			
	<b>Numeric value / percent of input amount (Air)</b>	50%	Y	Y
	<b>Justification of RFs (Air):</b>	<p>The value was assigned using a mass balance approach that takes advantage of the sector knowledge and professional judgement of individuals within the expert group responsible for creating this SpERC factsheet. The determination employs an informed decision-making process that assumed complete release of the chemical substances to the environment. Partitioning of the release to air, water, and soil takes into consideration the default release factors associated with ERC 8a. The assigned release factors were reviewed and agreed upon by a broad group of knowledgeable specialists within the sector organization (CEFIC, 2012).</p> <p>CEFIC (2012). Cefic Guidance Specific Environmental Release Categories (SPERCs) Chemical Safety Assessments, Supply Chain Communication and Downstream User Compliance. Revision 2, European Chemical Industry Council, Brussels, Belgium.</p> <p><a href="http://www.cefic.org/Documents/IndustrySupport/REACH-Implementation/Guidance-and-Tools/SPERCs-Specific-Environmental-Release-Classes.pdf">http://www.cefic.org/Documents/IndustrySupport/REACH-Implementation/Guidance-and-Tools/SPERCs-Specific-Environmental-Release-Classes.pdf</a>.</p>	Y	N
	<b>5.3.2 Release Factor – water</b>			
	<b>Numeric value / percent of input amount (Water):</b>	50%	Y	Y
	<b>Justification of RFs (Water):</b>	<p>The value was assigned using a mass balance approach that takes advantage of the sector knowledge and professional judgement of individuals within the expert group responsible for creating this SpERC factsheet. The determination employs an informed decision-making process that assumed complete release of the chemical substances to the environment. Partitioning of the release to air, water, and soil takes into consideration the default release factors associated with ERC 8a. The assigned release factors were reviewed and agreed upon by a broad group of knowledgeable specialists within the sector organization (CEFIC, 2012).</p> <p>CEFIC (2012). Cefic Guidance Specific Environmental Release Categories (SPERCs) Chemical Safety Assessments, Supply Chain Communication and Downstream User Compliance. Revision 2, European Chemical Industry Council, Brussels, Belgium.</p> <p><a href="http://www.cefic.org/Documents/IndustrySupport/REACH-Implementation/Guidance-and-Tools/SPERCs-Specific-Environmental-Release-Classes.pdf">http://www.cefic.org/Documents/IndustrySupport/REACH-Implementation/Guidance-and-Tools/SPERCs-Specific-Environmental-Release-Classes.pdf</a>.</p>	Y	N
	<b>5.3.3 Release Factor – soil</b>			
	<b>Numeric value / percent of input amount (Soil):</b>	0%	Y	Y
	<b>Justification of RFs (Soil):</b>	<p>The value was assigned using a mass balance approach that takes advantage of the sector knowledge and professional judgement of individuals within the expert group responsible for creating this SpERC factsheet. The determination employs an informed decision-making process that assumed complete release of the chemical substances to the environment. Partitioning of the release to air, water, and soil takes into</p>	Y	N

FS Section	Content field	Explanation of content	CSR <sup>1</sup>	eSDS <sup>2</sup>
		<p>consideration the default release factors associated with ERC 8a. The assigned release factors were reviewed and agreed upon by a broad group of knowledgeable specialists within the sector organization (CEFIC, 2012).</p> <p>CEFIC (2012). Cefic Guidance Specific Environmental Release Categories (SPERCs) Chemical Safety Assessments, Supply Chain Communication and Downstream User Compliance. Revision 2, European Chemical Industry Council, Brussels, Belgium.</p> <p><a href="http://www.cefic.org/Documents/IndustrySupport/REACH-Implementation/Guidance-and-Tools/SPERCs-Specific-Environmental-Release-Classes.pdf">http://www.cefic.org/Documents/IndustrySupport/REACH-Implementation/Guidance-and-Tools/SPERCs-Specific-Environmental-Release-Classes.pdf</a>.</p>		
<b>5.3.4 Release Factor – waste</b>				
	<b>Percent of input amount disposed as waste:</b>	50%	Y	N
	<b>Justification of RFs:</b>	<p>The solvent waste generated in research and analytical laboratories is generally accumulated and disposed of as hazardous waste. There has also been a recent trend toward the recovery and reuse of common laboratory solvents such as ethyl acetate, toluene, and acetonitrile (Stepnowski, P. et al., 2002; Zweckmair et al., 2017). When utilized, the solvent recovery efficiencies typically range from 50 to 95%. Since these recovery systems are not in widespread use, a substantial portion of the solvent waste from laboratories is collected for disposal in an incinerator. The waste release factor of 50% reflects the increasingly common implementation of recovery and reuse programs in many laboratories. Stepnowski, P. et al. (2002). Total recycling of chromatographic solvents—applied management of methanol and acetonitrile waste. Resources, Conservation and Recycling 35, 163-175.</p> <p>Zweckmair, T. et al. (2017). Recycling of analytical grade solvents on a lab scale with a purpose-built temperature-controlled distillation unit. Organic Process Research &amp; Development 21, 578-584.</p>	Y	N
<b>References to SPERC Background Document</b>				
	Reference to Background Document	ESIG/ESVOC (2019). SpERC Background Document (1 <sup>st</sup> draft). Specific Environmental Release Categories (SpERCs) for the professional use of solvents and solvent-borne substances in de-icing, construction, and laboratory applications. European Solvents Industry Group. Brussels, Belgium.	Y	N